

## BAT-Series

Grid Inverter. Battery Charger.

With the BAT-series, WSTECH offers a wide range of power converters for small to large energy storage applications.

The BAT-series inverters offer a power range from 20 kVA up to 1800 kVA with the following options and features:

- ✓ **Modbus TCP interface** that operates all control values, monitoring of all status values and overall configuration of the device. Modbus TCP is a wide-spread Ethernet-based fieldbus.
- ✓ **EtherCAT interface (Ethernet-based real time field bus)** prepared for active exchange of selected control and status values (configurable) in very fast control applications (millisecond-range).
- ✓ **Touch Display** for monitoring of selected status and configuration data, error messages review and on/off machine operation for maintenance work.
- ✓ **Internal Data Logger** capable of recording all status and control values with a sample time of 10 s for up to 1 year on the integrated USB-memory.
- ✓ **Grid stabilization** in compliance with local grid code.
- ✓ Supply of **reactive power** for different applications.
- ✓ **Outdoor models** available for demanding weather conditions.



## BAT-Series – Indoor

30 ... 280 kVA

### (I) TECHNICAL DATA

	BATI 20	BAT 50	BAT 100	BAT 280	COMMENTS
<b>GRID SIDE</b>					
Maximum AC-power ( $S_{max}$ )	30 kVA (for 10 s)	55 kVA	120 kVA (2 h)	280 kVA	At rated grid voltage
Rated AC-power ( $P_{N(AC)}$ )	20 kW	50 kW	100 kW	280 kW	At ( $\cos \phi$ ) = 1.0
Rated grid voltage ( $U_{N(AC)}$ )	1 x (400 V, 3~ + neutral, TN)				Other values on request
Rated grid frequency ( $f$ )	50 Hz				Other values on request
Maximum AC-current ( $I_{max(AC)}$ )	30 A	79 A	173 A	404 A	
Short circuit level ( $I_{SC(AC)}$ )	6 kA	36 kA			
Power factor ( $\cos \phi$ )	> 0.98				At > 20 % of rated power
AC-current distortion (THD)	< 3 %				
<b>BATTERY SIDE</b>					
Nominal voltage ( $U_{N(DC)}$ )	-	750 V <sub>DC</sub>			
Voltage range ( $U_{range(DC)}$ )	120 ... 375 V <sub>DC</sub>	530 ... 890 V <sub>DC</sub>	450 ... 890 V <sub>DC</sub>		
Currents ( $I_{range(DC)}$ )	+ / - 130 A	+ / - 110 A	+ / - 250 A	+ / - 630 A	
Maximum short circuit current ( $I_{SC(DC)}$ )	200 kA	40 kA			
Current THD	< 3 %				
Number of DC inputs	1				
<b>GENERAL</b>					
Control strategy	CC-CV, power controlled, island mode				
Efficiency in %	-	( 94.0   96.5   96.5   96.0   95.2 ) %	( 93.9   96.9   97.1   97.0   96.7 ) %	( 92.2   97.1   97.2   96.8   96.4 ) %	At ( 10   30   50   75   100 ) % power
Standby losses at night	< 6 W	< 30 W			
Maximum auxiliary power	< 120 W	< 250 W		< 600 W	Plus heating power
<b>MEASURING ACCURACY</b>					
Grid Frequency	+/- 20 mHz	+/- 40 mHz			Average value of 8 grid periods

## BAT-Series – Indoor

600 ... 1200 kVA

### (II) TECHNICAL DATA

	BATI 600	BATI 720	BATI 900	BATI 1200	COMMENTS
<b>GRID SIDE</b>					
<b>Maximum AC-power (<math>S_{max}</math>)</b>	600 kVA	720 kVA	900 kVA	2 x (600 kVA)	At rated grid voltage
<b>Rated AC-power (<math>P_{N(AC)}</math>)</b>	500 kW	615 kW	770 kW	2 x (500 kW)	At ( $\cos \phi$ ) = 1.0
<b>Rated grid voltage (<math>U_{N(AC)}</math>)</b>	1 x (270 V, 3~, IT)	1 x (300 V, 3~, IT)	1 x (380 V, 3~, IT)	2 x (270 V, 3~, IT)	Other values on request Recommendation of vector group: -Medium-voltage connection: Dd -Low-voltage connection: YNd or Yd -d: delta connection of inverter
<b>Rated grid frequency (<math>f</math>)</b>	50 Hz				Other values on request
<b>Maximum AC-current (<math>I_{max(AC)}</math>)</b>	1283 A	1385 A	1367 A	2 x (1283 A)	
<b>Short circuit level (<math>I_{SC(AC)}</math>)</b>	50 kA				
<b>Power factor (<math>\cos \phi</math>)</b>	> 0.98				At > 20 % of rated power
<b>AC-current distortion (THD)</b>	< 3 %				
<b>BATTERY SIDE&gt;</b>					
<b>Nominal voltage (<math>U_{N(DC)}</math>)</b>	750 V <sub>DC</sub>				
<b>Voltage range (<math>U_{range(DC)}</math>)</b>	450 ... 890 V <sub>DC</sub>	500 ... 890 V <sub>DC</sub>	630 ... 890 V <sub>DC</sub>	2 x (450 ... 890 V <sub>DC</sub> )	
<b>Currents (<math>I_{range(DC)}</math>)</b>	+ / - 1136 A	+ / - 1360 A	+ / - 1400 A	2 x (+/- 1136 A)	
<b>Maximum short circuit current (<math>I_{SC(DC)}</math>)</b>	6,4 kA				
<b>Current THD</b>	< 3 %				
<b>Number of DC inputs</b>	1			2	

## BAT-Series – Indoor

600 ... 1200 kVA

### (III) TECHNICAL DATA

	BATI 600	BATI 720	BATI 900	BATI 1200	COMMENTS
<b>GENERAL</b>					
<b>Control strategy</b>	CC-CV, power controlled, island mode				
<b>Efficiency in %</b>	( 97.1   97.5   97.5   97.3   97.1 ) %	( 97.4   97.9   97.9   97.7   97.5 ) %	( 97.6   98.0   98.0   97.8   97.6 ) %	( 97.1   97.5   97.5   97.3   97.1 ) %	At ( 10   30   50   75   100 ) % power
<b>Standby losses at night</b>	< 30 W			< 60 W	
<b>Maximum auxiliary power</b>	< 1000 W			< 2000 W	Plus heating power
<b>MEASURING ACCURACY</b>					
<b>Grid Frequency</b>	+/- 40 mHz				Average value of 8 grid periods

## BAT-Series – Indoor

1440 ... 1800 kVA

### (IV) TECHNICAL DATA

	BATI 1440	BATI 1800	COMMENTS
<b>GRID SIDE</b>			
Maximum AC-power ( $S_{max}$ )	2 x (720 kVA)	2 x (900 kVA)	At rated grid voltage
Rated AC-power ( $P_{N(AC)}$ )	2 x (615 kW)	2 x (770 kW)	At ( $\cos \phi$ ) = 1.0
Rated grid voltage ( $U_{N(AC)}$ )	2 x (300 V, 3~, IT)	2x (380 V, 3~, IT)	Other values on request Recommendation of vector group: -Medium-voltage connection: Dd -Low-voltage connection: YNd or Yd -d: delta connection of inverter
Rated grid frequency ( $f$ )	50 Hz		Other values on request
Maximum AC-current ( $I_{max(AC)}$ )	2 x (1385 A)	2 x (1367 A)	
Short circuit level ( $I_{SC(AC)}$ )	50 kA		
Power factor ( $\cos \phi$ )	> 0.98		At > 20 % of rated power
AC-current distortion (THD)	< 3 %		
<b>BATTERY SIDE</b>			
Nominal voltage ( $U_{N(DC)}$ )	750 V <sub>DC</sub>		
Voltage range ( $U_{range(DC)}$ )	2 x (500 ... 890 V <sub>DC</sub> )	2 x (630 ... 890 V <sub>DC</sub> )	
Currents ( $I_{range(DC)}$ )	2 x (+/- 1360 A)	2 x (+/- 1400 A)	
Maximum short circuit current ( $I_{SC(DC)}$ )	6,4 kA		
Current THD	< 3 %		
Number of DC inputs	2		

## BAT-Series – Indoor

1440 ... 1800 kVA

### (V) TECHNICAL DATA

	BATI 1440	BATI 1800	COMMENTS
<b>GENERAL</b>			
<b>Control strategy</b>	CC-CV, power controlled, island mode		
<b>Efficiency in %</b>	( 97.4   97.9   97.9   97.7   97.5 ) %	( 97.6   98.0   98.0   97.8   97.6 ) %	At ( 10   30   50   75   100 ) % power
<b>Standby losses at night</b>	< 60 W		
<b>Maximum auxiliary power</b>	< 2000 W		Plus heating power
<b>MEASURING ACCURACY</b>			
<b>Grid Frequency</b>	+/- 40 mHz		Average value of 8 grid periods

## BAT-Series – Outdoor

120 ... 280 kVA

### (I) TECHNICAL DATA

	BAT 100-400	BAT 100-480	BAT 280-400	BAT 280-480	COMMENTS
<b>GRID SIDE</b>					
<b>Maximum AC-power (<math>S_{max}</math>)</b>	120 kVA (2 h)		280 kVA		At rated grid voltage
<b>Rated AC-power (<math>P_{N(AC)}</math>)</b>	100 kW		280 kW		At ( $\cos \phi$ ) = 1.0
<b>Rated grid voltage (<math>U_{N(AC)}</math>)</b>	1 x (400 V, 3~ + neutral, TN)	1x (480Y / 277 V, solidly grounded wye , 3 phase, 4 wire)	1 x (400 V, 3~ + neutral, TN)	1x (480Y / 277 V, solidly grounded wye , 3 phase, 4 wire)	Other values on request
<b>Rated grid frequency (<math>f</math>)</b>	50 Hz	60 Hz	50 Hz	60 Hz	
<b>Maximum AC-current (<math>I_{max(AC)}</math>)</b>	173 A	144 A	404 A	337 A	
<b>Short circuit level (<math>I_{SC(AC)}</math>)</b>	36 kA	35 kA	36 kA	35 kA	
<b>Power factor (<math>\cos \phi</math>)</b>	> 0.98				At > 20 % of rated power
<b>AC-current distortion (THD)</b>	< 3 %				
<b>BATTERY SIDE</b>					
<b>Nominal voltage (<math>U_{N(DC)}</math>)</b>	750 V <sub>DC</sub>				
<b>Voltage range (<math>U_{range(DC)}</math>)</b>	450 ... 890 V <sub>DC</sub>				
<b>Currents (<math>I_{range(DC)}</math>)</b>	+ / - 250 A	+ / - 266 A	+ / - 630 A	+ / - 600 A	
<b>Maximum short circuit current (<math>I_{SC(DC)}</math>)</b>	40 kA	5 kA	40 kA	10 kA	
<b>Current THD</b>	< 3 %				
<b>Number of DC inputs</b>	1				
<b>GENERAL</b>					
<b>Control strategy</b>	CC-CV, power controlled, island mode				
<b>Efficiency in %</b>	( 93.9   96.9   97.1   97.0   96.7 ) %	( 93.9   96.9   97.1   97.0   96.7 ) %	( 92.2   97.1   97.2   96.8   96.4 ) %	( 92.2   97.1   97.2   96.8   96.4 ) %	At ( 10   30   50   75   100 ) % power
<b>Standby losses at night</b>	< 30 W				
<b>Maximum auxiliary power</b>	< 250 W		< 600 W		Plus heating power

## BAT-Series – Outdoor

120 ... 280 kVA

### (II) TECHNICAL DATA

	BAT 100-400	BAT 100-480	BAT 280-400	BAT 280-480	COMMENTS
<b>MEASURING ACCURACY</b>					
<b>DC-voltage</b>	-	1% of maximum DC-voltage	-	1% of maximum DC-voltage	
<b>AC-voltage</b>	-	1% of rated voltage	-	1% of rated voltage	
<b>DC-current</b>	-	1% of maximum DC-current	-	1% of maximum DC-current	
<b>AC-current</b>	-	1% of rated current	-	1% of rated current	
<b>Active Power (AC)</b>	-	2% of maximum AC-power	-	2% of maximum AC-power	
<b>Apparent Power (AC)</b>	-	2% of maximum AC-power	-	2% of maximum AC-power	
<b>Reactive Power (AC)</b>	-	2% of maximum AC-power	-	2% of maximum AC-power	
<b>Active Power (DC)</b>	-	2% of maximum DC-power	-	2% of maximum DC-power	
<b>Grid Frequency</b>	+/- 40 mHz				Average value of 8 grid periods



## BAT-Series – Indoor

30 ... 280 kVA

### (I) GENERAL DATA

	BATI 20	BAT 50	BAT 100	BAT 280	COMMENTS
<b>GENERAL</b>					
<b>Ambient temperature</b>	0 °C ... 40 °C	0 °C ... 50 °C			Other values on request
<b>Maximum humidity</b>	< 95 %				Not condensing
<b>Ambient storage temperature</b>	-	-25 °C ... 60 °C			
<b>Storage relative humidity</b>	-	< 90 %			Not condensing
<b>Maximum operating altitude</b>	1500 m above sea level				Without power derating
<b>Cooling type</b>	Forced air				
<b>Air cooling volume</b>	360 m <sup>3</sup> /h	800 m <sup>3</sup> /h	1500 m <sup>3</sup> /h	3000 m <sup>3</sup> /h	Class 3S2 (EN60721-3-3)
<b>Protection class</b>	IP20				
<b>Dimensions (Length x Width x Height)</b>	19 inch rack, 7 RU	611 x 647 x 1902	1009 x 862 x 1903	1409 x 846 x 1906	In mm
<b>Weight</b>	< 60 kg	< 800 kg	< 1050 kg	< 1600 kg	
<b>Color</b>	Aluminum	RAL7035			Others on request
<b>Noise Level</b>	< 70 dBA	< 80 dBA			
<b>EMI</b>	EN61000-6-2, EN61000-6-4				
<b>Medium voltage directive</b>	-	BDEW			Others on request
<b>Low voltage directive</b>	VDE-AR-N 4105				
<b>CE-conformity</b>	Comply				

## BAT-Series – Indoor

600 ... 1200 kVA

### (II) GENERAL DATA

	BATI 600	BATI 720	BATI 900	BATI 1200	COMMENTS
<b>GENERAL</b>					
Ambient temperature	0 °C ... 50 °C				Other values on request
Maximum humidity	< 95 %				Not condensing
Ambient storage temperature	-25 °C ... 60 °C				
Storage relative humidity	< 90 %				Not condensing
Maximum operating altitude	1500 m above sea level				Without power derating
Cooling type	Forced air				
Air cooling volume	3600 m <sup>3</sup> /h		2 x (3600 m <sup>3</sup> /h)		Class 3S2 (EN60721-3-3)
Protection class	IP20				
Dimensions (Length x Width x Height)	1813 x 867 x 2172		3260 x 867 x 2172		In mm
Weight	< 1600 kg		< 2950 kg		
Color	RAL7035				Others on request
Noise Level	< 80 dBA				
EMI	EN61000-6-2, EN61000-6-4				
Medium voltage directive	BDEW				Others on request
Low voltage directive	-				
CE-conformity	Comply				

## BAT-Series – Indoor

1440 ... 1800 kVA

### (III) GENERAL DATA

	BATI 1440	BATI 1800	COMMENTS
<b>GENERAL</b>			
Ambient temperature	0 °C ... 50 °C		Other values on request
Maximum humidity	< 95 %		Not condensing
Ambient storage temperature	-25 °C ... 60 °C		
Storage relative humidity	< 90 %		Not condensing
Maximum operating altitude	1500 m above sea level		Without power derating
Cooling type	Forced air		
Air cooling volume	2 x (3600 m³/h)		Class 3S2 (EN60721-3-3)
Protection class	IP20		
Dimensions (Length x Width x Height)	3260 x 867 x 2172		In mm
Weight	< 2950 kg		
Color	RAL7035		Others on request
Noise Level	< 80 dBA		
EMI	EN61000-6-2, EN61000-6-4		
Medium voltage directive	BDEW		Others on request
Low voltage directive	-		
CE-conformity	Comply		

## BAT-Series – Outdoor

120 ... 280 kVA

### GENERAL DATA

	BAT 100-400	BAT 100-480	BAT 280-400	BAT 280-480	COMMENTS
<b>GENERAL</b>					
<b>Ambient temperature</b>	-20 °C ... 50 °C	-10 °C ... 50 °C (14 °F ... 122 °F)	-20 °C ... 50 °C	-10 °C ... 50 °C (14 °F ... 122 °F)	Other values on request
<b>Maximum humidity</b>	100 %				Not condensing
<b>Ambient storage temperature</b>	-25 °C ... 60 °C				
<b>Storage relative humidity</b>	< 90 %				Not condensing
<b>Maximum operating altitude</b>	1500 m above sea level				Without power derating
<b>Cooling type</b>	Forced air				
<b>Air cooling volume</b>	1500 m <sup>3</sup> /h		3000 m <sup>3</sup> /h		Class 3S2 (EN60721-3-3)
<b>Protection class</b>	IP44	NEMA 3R	IP44	NEMA 3R	
<b>Dimensions (Length x Width x Height)</b>	1152 x 1250 x 2249		1597 x 1353 x 2249		In mm
<b>Weight</b>	< 950 kg		< 2000 kg		
<b>Color</b>	RAL7035				Others on request
<b>Noise Level</b>	< 80 dBA				
<b>EMI</b>	EN61000-6-2, EN61000-6-4	-	EN61000-6-2, EN61000-6-4	-	
<b>Medium voltage directive</b>	BDEW	-	BDEW	-	Others on request
<b>Low voltage directive</b>	VDE-AR-N 4105	-	VDE-AR-N 4105	-	
<b>CE-conformity</b>	Comply	-	Comply	-	
<b>UL 1741:2010 + SA:2016</b>	-	Comply	-	Comply	
<b>CSA Standard, C22.2 No. 107.1-01: 2011</b>	-	Comply	-	Comply	
<b>CEC Guideline</b>	-	Comply	-	Comply	

## BAT-Series – Indoor

30 ... 600 kVA

### (I) FEATURES AND OPTIONS

	BATI 20	BAT 50	BAT 100	BAT 280	BATI 600
<b>FEATURES</b>					
Overvoltage protection	-	X	X	X	X
Earth leakage monitor with adjustable limit	-	X	X	X	X
Enable switch	-	X	X	X	X
DC-disconnector	X	-	-	-	X
DC-circuit breaker	-	X	X	X	-
DC-contactor with fuses	X	-	-	-	-
AC-circuit breaker	-	X	X	X	X
Modbus TCP interface	-	X	X	X	X
CAN interface	X	-	-	-	-
Internal data logger	-	X	X	X	X
<b>OPTIONS</b>					
Island grid function	O	O	O	O	O
Interface for SBB16-10	-	O	O	O	-
Cabinet heating	-	O	O	O	O
EtherCAT interface	-	O	O	O	O
Graphical display (HMI)	-	O	O	O	-

X = included

- = not included / not available

O = optional

## BAT-Series – Indoor

720 ... 1800 kVA

### (II) FEATURES AND OPTIONS

	BATI 720	BATI 900	BATI 1200	BATI 1440	BATI 1800
<b>FEATURES</b>					
Overvoltage protection	X	X	X	X	X
Earth leakage monitor with adjustable limit	X	X	X	X	X
Enable switch	X	X	X	X	X
DC-disconnector	X	X	X	X	X
DC-circuit breaker	-	-	-	-	-
DC-contactor with fuses	-	-	-	-	-
AC-circuit breaker	X	X	X	X	X
Modbus TCP interface	X	X	X	X	X
CAN interface	-	-	-	-	-
Internal data logger	X	X	X	X	X
<b>OPTIONS</b>					
Island grid function	O	O	O	O	O
Interface for SBB16-10	-	-	-	-	-
Cabinet heating	O	O	O	O	O
EtherCAT interface	O	O	O	O	O
Graphical display (HMI)	-	-	-	-	-

X = included

- = not included / not available

O = optional

## BAT-Series – Outdoor

120 ... 280 kVA

### FEATURES AND OPTIONS

	BAT 100-400	BAT 100-480	BAT 280-400	BAT 280-480
<b>FEATURES</b>				
Overvoltage protection	X	X	X	X
Earth leakage monitor with adjustable limit	X	X	X	X
Enable switch	X	X	X	X
DC-disconnector	-	-	-	-
DC-circuit breaker	X	X	X	X
DC-contactor with fuses	-	-	-	-
AC-circuit breaker	X	X	X	X
Modbus TCP interface	X	X	X	X
CAN interface	-	-	-	-
Internal data logger	X	X	X	X
Cabinet heating	X	X	X	X
<b>OPTIONS</b>				
Island grid function	O	O	O	O
Interface for SBB16-10	-	-	-	-
EtherCAT interface	O	O	O	O
Graphical display (HMI)	-	-	-	-

X = included

- = not included / not available

O = optional

## BAT-Series – Indoor

30 ... 120 kVA

### (I) MECHANICAL DRAWINGS

BATI 20



19 inch rack - 7 RU

BAT 50



BAT 100





## BAT-Series – Indoor

280 ... 900 kVA

### (II) MECHANICAL DRAWINGS

BAT 280



BATI 600 / BATI 720 / BATI 900



## BAT-Series – Indoor

1200 ... 1800 kVA

### (III) MECHANICAL DRAWINGS

BATI 1200 / BATI 1400 / BATI 1800



## BAT-Series – Outdoor

120 ... 280 kVA

### MECHANICAL DRAWINGS

BAT 100-400 / BAT 100-480



BAT 280-400 / BAT 280-480



## BAT-Series

30 ... 1800 kVA

### EQUIVALENT MODEL NAME

BAT-Series – INDOOR	
BATI 20	BATI0020
BAT 50	BATD0050-ES-1-400-1
BAT 100	BATx0100-ES-1-400-1
BAT 280	BATx0280-ES-1-400-1
BATI 600	BATI0600-ES-1-270-1
BATI 720	BATI0720-ES-1-300-1
BATI 900	BATI0900-ES-1-380-1
BATI 1200	BATI1200-ES-2-270-1
BATI 1440	BATI1440-ES-2-300-1
BATI 1800	BATI1800-ES-2-380-1

BAT-Series – OUTDOOR	
BAT 100-400	BATx0100-ES-1-400-1 (Outdoor)
BAT 100-480	BATD0100-ES-1-480-1 (Outdoor)
BAT 280-400	BATx0280-ES-1-400-1 (Outdoor)
BAT 280-480	BATD0280-ES-1-480-1 (Outdoor)

## CONTACT

### SALES DEPARTMENT GERMANY

**WSTECH GmbH**

Eckernfoerder Landstrasse, 78  
D-24941 Flensburg · Germany

**Phone** +49 (0) 461 430 1220

**E-Mail** [info@wstech.com](mailto:info@wstech.com)

### SALES DEPARTMENT WORLDWIDE

**WSTECH (Spanish office)**

Carrer de l'Enginy, Nave 7  
E-08840 Viladecans (Barcelona) · Spain

**Phone** +34 936 334 416

**E-Mail** [info@wstech.com](mailto:info@wstech.com)

Datasheet version **Datasheet\_BAT-Series\_V24.2\_eng**. © Copyright 2018. All rights reserved.

Specifications subject to change without notice. WSTECH assumes no liability for typographical or other errors.  
All Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.